



NORTHEAST
— PNEUMATICS —

SUNNY PRESSURE SWITCHES

Air Compressor Pressure Switches



SINGLE PORT / FOUR PORT

The LF-SU pressure switch has a minimum close cut-in of 40, and a max open cut-out of 150 with a differential range of 30-40. The pressure switch is suitable for a single phase 115V 1-1/2 HP motor, a single phase 230V 2 HP motor, and a 3 phase 230V 3 HP motor. Factory setting is 95-125. Includes on/off lever and unloader.

- Corrosion Resistant and Non Metallic Cover
- Ample Wiring Room
- 2 Ground Screw
- Visible Contact
- Easy to Adjust
- No Drift Pressure Setting
- Automatic Unloader Valve Standard
- No Wire Looping
- Pulsation Dampener Standard
- Captive Cover Screw
- On/Off Lever Standard

MODEL	Min ON (Cut-In) PSI	Max Off (Cut-Out) PSI	Differential PSI	Factory Setting PSI	Electrical Rating		Pipe Fittings Female NPT	Contact Arrangement
					120VAC	240VAC		
LF-SU-L1	35	150	30-40	95-125	25A	25A	1/4"	NC
LF-SU-H1	50	175	35-55	145-175	25A	25A	1/4"	NC
LF-SU-L4	35	150	30-40	95-125	25A	25A	1/4"	NC
LF-SU-H4	50	175	35-55	145-175	25A	25A	1/4"	NC

COMPRESSED AIR SPECIALIST

SUNNY PRESSURE SWITCHES