



NORTHEAST
— PNEUMATICS —

SUNNY PRESSURE SWITCH

Air Compressor Pressure Switches



Heavy Duty 25 Amp Single Port

The SU-MH1 is a 25 amp heavy duty pressure switch that is used to regulate tank pressures. The contact is heavy duty and is enclosed in a metal enclosure with a captive cover screw. The pressure settings are minimum close / cut-in of 60 psig and a max open / cut-out of 200 psig with an easy adjustable differential range of 28-40. Factory setting is 140-175 psig. The pressure switch is suitable for a single phase 115V 1-1/2 HP motor, a single phase 230V 2 HP motor, or 3 phase 230V 3 HP motor.

- Metallic Cover
- Ample Wiring Room
- Visible Contact
- Easy to Adjust
- No Drift Pressure Setting
- Automatic Unloader Valve Standard
- No Wire Looping
- Pulsation Dampener Standard
- Captive Cover Screw



MODEL	Min ON (Cut-In) PSI	Max Off (Cut-Out) PSI	Differential PSI	Factory Setting PSI	Electrical Rating		Pipe Fittings Female NPT	Contact Arrangement
					120VAC	240VAC		
SU-MH1	60	200	28-40	140-175	25A	25A	1/4"	NC

COMPRESSED AIR SPECIALIST

SUNNY PRESSURE SWITCH